


# XT402 / XT602 - LED LIGHTS



Available Colors - Red, Amber, Blue, White and Green

## WIRING INSTRUCTIONS:

To +VDC (fuse @ 3A) ----- **RED**  
To Chassis Ground ----- **BLACK**  
Flash Pattern Select (see list at right) ----- **BLUE**

Connect **YELLOW** wires of all heads together for  
Synchronization ----- **YELLOW**

**\*When the Yellow wires of all heads are connected together, the Group1 heads will flash either in phase (P1) or 180 degrees out of phase (P2) based on the pattern selected. For example, if the XT3 lights in Group1 have pattern PA1, A1-Five Flash P1 selected and the Group2 heads have pattern PA2, A2-Five Flash P2 selected, the Group1 / Group2 heads will flash in a Five Flash Alternating (WIG/WAG) mode.**

Mount the XTxxx LED light using the brackets supplied and user supplied mounting screws. Be sure that the unit is properly fused.

**CAUTION:** Be certain that you have selected a mounting location that will not interfere with the deployment of the vehicle's airbags, does not obstruct the driver's vision and allows safe operation of the vehicle. Check the chosen mounting location to ensure that the vehicle's structure and material is adequate to support the weight of your light.

After the XT402 or XT602 light is securely installed, loosen the adjusting screws Located on each end and tilt the light to the desired angle. Then tighten the screws. Turn the light on and check the light from the front or rear of the vehicle, through the window, to ensure that it is at the most desirable angle, and that the light is not impeded by any obstacles and/or window tinting.

## FLASH PATTERNS:

- P1 five flash alt
- P2 five flash sim p1
- P3 five flash sim p2
- P4 quad flash alt
- P5 quad flash sim p1
- P6 quad flash sim p2
- P7 single flash 75 alt
- P8 single flash 75 sim p1
- P9 single flash 75 sim p2
- P10 single flash 375 alt
- P11 single flash 375 sim p1
- P12single flash 375simp2
- P13quad-squad flash alt
- P14quad-squad flashsim
- P15modulation flash alt
- P16modulation flashsim
- P17quad-squad scan
- P18steadyburn with 5 single & 1 single
- P19steadyburn - 5 single
- P20steady burn
- P21Cycle Flash - AUTORUN
- P22off

To select Flash Pattern briefly touch the ,  
BLUE to BLACK wire (Ground):

- less than 1 second for next pattern
- more than 1 second for previous pattern
- more than 5 seconds to turn off

## WARNING!



This Product contains high intensity LED devices. To prevent eye damage, DO NOT stare into light beam at close range.

# WARRANTY

Code 3, Inc.'s emergency devices are tested and found to be operational at the time of manufacture. Provided they are installed and operated in accordance with manufacturer's recommendations, Code 3, Inc. guarantees all parts and components except the lamps to a period of 1 year, LED Lighthouse modules to a period of 5 years (unless otherwise expressed) from the date of purchase or delivery, whichever is later. Units demonstrated to be defective within the warranty period will be repaired or replaced at the factory service center at no cost.

Use of lamp or other electrical load of a wattage higher than installed or recommended by the factory, or use of inappropriate or inadequate wiring or circuit protection causes this warranty to become void. Failure or destruction of the product resulting from abuse or unusual use and/or accidents is not covered by this warranty. Code 3, Inc. shall in no way be liable for other damages including consequential, indirect or special damages whether loss is due to negligence or breach of warranty.

**CODE 3, INC. MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY INCLUDING, WITHOUT LIMITATION, WARRANTIES OF FITNESS OR MERCHANTABILITY, WITH RESPECT TO THIS PRODUCT.**

# PRODUCT RETURNS

If a product must be returned for repair or replacement\*, please contact our factory to obtain a Return Goods Authorization Number (RGA number) before you ship the product to Code 3, Inc. Write the RGA number clearly on the package near the mailing label. Be sure you use sufficient packing materials to avoid damage to the product being returned while in transit.

\*Code 3, Inc. reserves the right to repair or replace at its discretion. Code 3, Inc. assumes no responsibility or liability for expenses incurred for the removal and /or reinstallation of products requiring service and/or repair.; nor for the packaging, handling, and shipping; nor for the handling of products returned to sender after the service has been rendered.

 **CODE 3**<sup>®</sup>  
A PUBLIC SAFETY EQUIPMENT COMPANY

**NEED HELP? Call our Technical Assistance HOTLINE - (314) 996-2800**

Code 3®, Inc.  
10986 N. Warson Road  
St. Louis, Missouri 63114-2029—USA  
Ph. (314) 426-2700 Fax (314) 426-1337  
[www.code3pse.com](http://www.code3pse.com)