

45R-L6



## Remote Rocker Max Pak™ Switch

### Benefits

- Allows user to easily program, customize, and control unique warning packages with a single rocker switch box
- Simplifies installation with a compact, lightweight switch box that can be mounted in small, tight spaces, e.g., trunk, under seat, behind second row truck bench
- Allows user to quickly identify and switch through functions with a backlit controller

### Design Features

- Top three buttons can be programmed as progressive level 1, 2, 3 outputs
- All six can be programmed as independent momentary, on/off, and timed output (8 sec)
- Rubber membrane buttons are backlit in blue lighting
- Fuse box located on top of switch box for easy accessibility
- 15 foot cable between controller and switch box
- Swivel style bracket or mount

### Specifications

- Switch Box: 5.2" W x 5.3" L x 1.5" D (132 x 135 x 38 mm)
- Control head: 2" W x 3.9" L x 0.9" D (51 x 99 x 23 mm)
- 12VDC
- Switch box: Four-hole flange mounting on base
- Controller: Two mounting holes provided on controller bracket
- One 40 ampere and five 15 ampere connections
- SAE J575 Environmental
- Two-year warranty
- Switch Box: 1.1 lbs
- Controller: 0.2 lbs
- Standby Current: 85 mA
- Operation Temperature: -40°C (40°F) to +77°C (170°F)

