

Multifunctional, Resilient Perimeter Light

Outliner™ Perimeter Bar



Benefits

- Allows installation on running boards, push bumpers, tailgates or any other perimeter location
- Distributes a bright output to increase vehicle visibility on a broad range of emergency vehicles from sedans to large trucks
- Features a high grade powder coated aluminum housing and sealed lighthead that prevent corrosion and water ingress

Design Features

- Available in amber, blue, red, and white
- Split and solid color combinations
- 10 flash patterns, including dim and steady burn override
- Universal, versatile mounting capabilities
- Powder coated aluminum frame
- IP67 rated for dust and water resistance
- Phase 1 and phase 2 syncing capabilities
- 55" cable enclosed in a jacket

Length	Max Watts	Max Ampere
24" (610 mm)	3.71	0.29
36" (914 mm)	7.30	0.57
60" (1524 mm)	8.19	0.64
72" (1829 mm)	13.70	1.07

- 60" (1524 mm) lengths are recommended for Chevy Chargers, Ford Police Interceptor Utilities, and Chevy Tahoes running boards
- 72" (1829 mm) lengths are recommended for pickup truck running boards



C3RNR

Specifications



0.6" H x 2.1" D (16 x 54 mm)
Available in 24", 36", 60" and 72" (610, 914, 1524, 1829 mm)



12VDC



Temperature range: -40°F to 170°F (-40°C to 77°C)



RoHS and IP67 rated



5-year warranty

Colors



Single
Color
LEDs

4 Sizes



A variety of applications