

XT402xxSS, XT602xxSS LED WARNING LIGHTS



XT402xxSS



XT602xxSS



Input Voltage(Fuse 3A)-----12Vdc/24Vdc(PLUG)
Flash Pattern Select-----SWITCH
Output Power-----8W(402xxSS)/12W(602xxSS)

Before mounting the warning lights, clean the lighter socket and contact surfaces. Using the Suction Cups supplied, mount the XT402xxSS/XT602xxSS LED light to the windshield.

CAUTION: Be sure the mount and/or fasteners used are sufficient to support the weight of your light.

CAUTION: Be certain that you have selected a mounting location that will not interfere with the deployment of the vehicle's airbags, does not obstruct the driver's vision and allows safe operation of the vehicle. Check the chosen mounting location to ensure that the vehicle's structure and material is adequate to support the weight of your light.

After the XT402xxSS or XT602xxSS light is securely installed, loosen the adjusting screws Located on each end and tilt the light to the desired angle. Then tighten the fixed hitch. Turn the light on and check the light from the front or rear of the vehicle, through the windows, to ensure that it is at the most desirable angle, and that the light is not impeded by any obstacles and/or window tinting.

Model XT-402xxSS,XT-602xxSS FLASH PATTERN

- P1- signal alert alternating (factory Default)
- P2- signal alert simultaneous phase1
- P3- signal alert simultaneous phase2
- P4- cometflash alternating
- P5- cometflash simultaneous phase1
- P6- cometflash simultaneous phase2
- P7-single flash75 alternating
- P8-single flash75 simultaneous phase1
- P9-single flash75 simultaneous phase2
- P10- single flash375 alternating
- P11- single flash375 simultaneous phase1
- P12-single flash375 simultaneous phase2
- P13-action flash alternating
- P14-action flash simultaneous
- P15-modul flash alternating
- P16-modul flash simultaneous
- P17-action scan
- P18- STEADY WITH 5 SINGLE AND SINGLE POP
- P19- STEADY - 5 SINGLE
- P20- STEADY
- P21- Cycle Flash- AUTORUN
- P22- off

To select flash Pattern briefly Push the Function SWITCH on end of Light:

- less than 1 second for next pattern
- more than 1 second for previous pattern
- more than 5 seconds to turn off

IMPORTANT: Please be sure to check that the product is properly fused. Installing the XT402xxSS/XT602xxSS LED light without the appropriate fuse will void the warranty.

WARNING!



This Product contains high intensity LED devices. To prevent eye damage, DO NOT stare into light beam at close range.

WARRANTY

Code 3®, Inc.'s emergency devices are tested and found to be operational at the time of manufacture. Provided they are installed and operated in accordance with manufacturer's recommendations, Code 3®, Inc. guarantees all parts and components except the lamps to a period of 1 year, LED Lighthouse modules to a period of 5 years (unless otherwise expressed) from the date of purchase or delivery, whichever is later. Units demonstrated to be defective within the warranty period will be repaired or replaced at the factory service center at no cost.

Use of lamp or other electrical load of a wattage higher than installed or recommended by the factory, or use of inappropriate or inadequate wiring or circuit protection causes this warranty to become void. Failure or destruction of the product resulting from abuse or unusual use and/or accidents is not covered by this warranty. Code 3®, Inc. shall in no way be liable for other damages including consequential, indirect or special damages whether loss is due to negligence or breach of warranty.

CODE 3®, INC. MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY INCLUDING, WITHOUT LIMITATION, WARRANTIES OF FITNESS OR MERCHANTABILITY, WITH RESPECT TO THIS PRODUCT.

PRODUCT RETURNS

If a product must be returned for repair or replacement*, please contact our factory to obtain a Return Goods Authorization Number (RGA number) before you ship the product to Code 3®, Inc. Write the RGA number clearly on the package near the mailing label. Be sure you use sufficient packing materials to avoid damage to the product being returned while in transit.

*Code 3®, Inc. reserves the right to repair or replace at its discretion. Code 3®, Inc. assumes no responsibility or liability for expenses incurred for the removal and/or reinstallation of products requiring service and/or repair; nor for the packaging, handling, and shipping; nor for the handling of products returned to sender after the service has been rendered.

For Technical Support / Service, please call 314-996-2800.

Code 3®, Inc.
10986 N. Warson Road
St. Louis, Missouri 63114-2029—USA
Ph. (314) 426-2700 Fax (314) 426-1337
www.code3pse.com